

CHAPTER IV. BUILDINGS AND CONSTRUCTION

ARTICLE 2. BUILDING CODE

SECTIONS

- 4-201 INTERNATIONAL BUILDING CODE ADOPTED.
- 4-202 INTERNATIONAL BUILDING CODE, SECTION 101.1. TITLE.
- 4-203 INTERNATIONAL BUILDING CODE, SECTION 101.4.1. SCOPE.
- 4-204 INTERNATIONAL BUILDING CODE, SECTION 102.6, APPLICABILITY, EXISTING STRUCTURES.
- 4-205 INTERNATIONAL BUILDING CODE, SECTION 104.1. DUTIES AND POWERS OF THE BUILDING OFFICIAL, GENERAL.
- 4-206 INTERNATIONAL BUILDING CODE, SECTION 104.10 MODIFICATIONS.
- 4-207 INTERNATIONAL BUILDING CODE, SECTION 104.11. ALTERNATIVE MATERIALS, DESIGN AND METHOD OF CONSTRUCTION AND EQUIPMENT.
- 4-208 INTERNATIONAL BUILDING CODE, SECTION 105.2. WORK EXEMPTED FROM PERMIT.
- 4-209 INTERNATIONAL BUILDING CODE, SECTION 105.3. APPLICATION FOR PERMIT.
- 4-210 INTERNATIONAL BUILDING CODE, SECTION 105.5. EXPIRATION.
- 4-211 INTERNATIONAL BUILDING CODE, SECTION 107.1. SUBMITTAL DOCUMENTS, GENERAL.
- 4-212 INTERNATIONAL BUILDING CODE, SECTION 107.2.2. FIRE PROTECTION SYSTEM SHOP DRAWINGS.
- 4-213 INTERNATIONAL BUILDING CODE, SECTION 107.2.5. SITE PLAN.
- 4-214 INTERNATIONAL BUILDING CODE, SECTION 108.1. GENERAL.
- 4-215 INTERNATIONAL BUILDING CODE, SECTION 108.2. CONFORMANCE. *REPEALED.*
- 4-216 INTERNATIONAL BUILDING CODE, SECTION 108.3. TEMPORARY POWER. *REPEALED.*
- 4-217 INTERNATIONAL BUILDING CODE, SECTION 109.2. SCHEDULE OF PERMIT FEES.
- 4-218 INTERNATIONAL BUILDING CODE, SECTION 109.6. REFUNDS.
- 4-219 INTERNATIONAL BUILDING CODE, SECTION 109.3. REQUIRED INSPECTIONS.
- 4-220 INTERNATIONAL BUILDING CODE, SECTION 111.1. USE AND OCCUPANCY.
- 4-221 INTERNATIONAL BUILDING CODE, SECTION 111.2. CERTIFICATE ISSUED.
- 4-222 INTERNATIONAL BUILDING CODE, SECTION 111.3. TEMPORARY OCCUPANCY.
- 4-223 INTERNATIONAL BUILDING CODE, SECTION 112.3. AUTHORITY TO DISCONNECT SERVICE UTILITIES.
- 4-224 INTERNATIONAL BUILDING CODE, SECTION 113. BOARD OF APPEALS.
- 4-225 INTERNATIONAL BUILDING CODE, SECTION 114.4. VIOLATION PENALTIES.
- 4-226 INTERNATIONAL BUILDING CODE, SECTION 116. UNSAFE STRUCTURES AND EQUIPMENT. *REPEALED.*
- 4-226A INTERNATIONAL BUILDING CODE, SECTION 305.2.3. SIX OR FEWER CHILDREN IN A DWELLING UNIT.4-226B INTERNATIONAL BUILDING CODE, SECTION 423.2. STORM SHELTERS, GENERAL.
- 4-226C INTERNATIONAL BUILDING CODE, SECTION 423.4. GROUP E, R-1, R-2, R-3, R-4, I-1, OR I-2 OCCUPANCIES.
- 4-226D INTERNATIONAL BUILDING CODE, SECTION 423.4.1. REQUIRED OCCUPANT CAPACITY.
- 4-226E INTERNATIONAL BUILDING CODE, SECTION 429. BASEMENT REQUIRED.
- 4-227 INTERNATIONAL BUILDING CODE, SECTION 903.2. WHERE REQUIRED AUTOMATIC SPRINKLER SYSTEMS.
- 4-227A INTERNATIONAL BUILDING CODE, SECTION 903.3. INSTALLATION REQUIREMENTS.
- 4-228 INTERNATIONAL BUILDING CODE, SECTION 905.3. GENERAL.
- 4228A INTERNATIONAL BUILDING CODE, TABLE 1004.1.2. MAXIMUM FLOOR AREA ALLOWANCES PER OCCUPANT. *REPEALED.*

- 4-229 INTERNATIONAL BUILDING CODE, SECTION 1010.4. PHYSICAL SECURITY.
- 4-230 INTERNATIONAL BUILDING CODE, SECTION 1010.4.1. SCOPE.
- 4-231 INTERNATIONAL BUILDING CODE, SECTION 1010.4.2. DOORS.
- 4-232 INTERNATIONAL BUILDING CODE, SECTION 1010.4.3. DOOR FRAMES.
- 4-233 INTERNATIONAL BUILDING CODE, SECTION 1010.4.4. DOOR HARDWARE.
- 4-234 INTERNATIONAL BUILDING CODE, SECTION 1010.4.5. STREET NUMBERS.
- 4-235 INTERNATIONAL BUILDING CODE, SECTION 1010.4.6. EXTERIOR LIGHTING.
- 4-236 INTERNATIONAL BUILDING CODE, SECTION 1016.2. EGRESS THROUGH INTERVENING SPACES.
- 4-236A INTERNATIONAL BUILDING CODE, SECTION 1202.1. VENTILATION GENERAL.
- 4-237 INTERNATIONAL BUILDING CODE, SECTION 1501.1. SCOPE.
- 4-237A INTERNATIONAL BUILDING CODE, SECTION 1511.1. GENERAL.
- 4-237B INTERNATIONAL BUILDING CODE, SECTION 1612.3. ESTABLISHMENT OF FLOOD HAZARD AREAS.
- 4-238 INTERNATIONAL BUILDING CODE, TABLE 2902.1. MINIMUM NUMBER OF REQUIRED PLUMBING FIXTURES.
- 4-239 INTERNATIONAL BUILDING CODE, SECTION 3001.6. ACCEPTANCE INSPECTIONS.
- 4-240 INTERNATIONAL BUILDING CODE, SECTION 3001.7. PERIODIC INSPECTIONS.
- 4-240A INTERNATIONAL BUILDING CODE, SECTION 3001.8. CERTIFICATION OF INSPECTION REQUIRED.
- 4-240B INTERNATIONAL BUILDING CODE, SECTION 3001.9. EXISTING ELEVATORS.
- 4-241 INTERNATIONAL BUILDING CODE, SECTION 3403.6. ELEVATORS. *REPEALED.*
- 4-241A INTERNATIONAL BUILDING CODE, SECTION 3404.7. ELEVATORS. *REPEALED.*
- 4-242 INTERNATIONAL BUILDING CODE, SECTION 3410.2. LEAWOOD DEVELOPMENT ORDINANCE CONFORMANCE. *REPEALED.*
- 4-243 INTERNATIONAL BUILDING CODE, SECTION 3410.3. DUTIES OF STRUCTURE MOVING PERMITTEE. *REPEALED.*

4-201. INTERNATIONAL BUILDING CODE ADOPTED. There is hereby incorporated by reference that certain code known as the International Building Code, 2018 edition, ["IBC"] prepared and published in book form by the International Code Council, Inc., including appendices C, G and I save and except such articles, sections, parts or portions as are hereafter omitted, deleted, amended, modified or changed or added thereto, such incorporation being authorized by K.S.A. § 12-3009 through 12-3012, as amended. At least one copy of said Code shall be marked or stamped "Official copy as incorporated by Ordinance No. 2978," with all sections or portions thereof intended to be omitted or changed clearly marked to show any such omission or change and to which shall be attached a copy of this ordinance, and filed with the City Clerk to be open to inspection and available to the public at all reasonable hours.

(Ord. 2978; 01-21-20)
 (Ord. 2593C; 12-03-12)
 (Ord. 2291C; 02-04-08)
 (Ord. 1930C; 01-22-02)
 (Code 2000)
 (Ord. 1711C; 03-23-98)

4-202. INTERNATIONAL BUILDING CODE, SECTION 101.1. TITLE. Section 101.1 of the IBC is hereby amended to read as follows: **Title.** These regulations shall be known and referred to as this code, the IBC or the Building Code of the City of Leawood, Kansas.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

4-203. INTERNATIONAL BUILDING CODE, SECTION 101.2. SCOPE. Section 101.2 of the IBC is hereby amended to read as follows: **Scope.** The provisions of this code and the Leawood Development Ordinance shall apply to the construction, alteration, relocation, enlargement, replacement, repair, equipment use and occupancy, location, maintenance, removal and demolition of every building or structure or any appurtenances connected or attached to such buildings or structures.

EXCEPTION: Detached one- and two-family dwellings and townhouses not more than three stories above grade plane in height with a separate means of egress and their accessory structures shall comply with the International Residential Code and the Leawood Development Ordinance.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

4-204. INTERNATIONAL BUILDING CODE, SECTION 102.6. APPLICABILITY, EXISTING STRUCTURES. Section 102.6 of the IBC is hereby amended to read as follows: **Existing structures.** The legal occupancy of any structure existing on the date of adoption of this Building Code shall be permitted to continue without change, except as is specifically covered in the Leawood Development Ordinance, the Code of the City of Leawood, this Building Code, the *Property Maintenance Code (Chapter VIII)* or the *Leawood Fire Protection Code (Chapter VII)*, or as is deemed necessary by the building official for the general safety and welfare of the occupants and the public.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

4-205. INTERNATIONAL BUILDING CODE, SECTION 104.1. DUTIES AND POWERS OF THE BUILDING OFFICIAL, GENERAL. Section 104.1 of the IBC is hereby amended to read as follows: **General.** The Building Official is hereby authorized and directed to enforce the provisions of this Building Code. The Building Official shall have the authority to render interpretations of this Building Code and to adopt policies and procedures in order to clarify the application of its provisions. Such interpretations, policies, and procedures shall comply with the intent and purpose of this Building Code. Such policies and procedures shall not have the effect of waiving requirements specifically provided for in this Building Code. The Building Official shall be known as the codes administrator, and such term shall include his/her authorized representatives. Further, whenever the term or title "administrative authority," "code enforcement officer," "responsible official," "codes administrator," or other similar designation is used in any of the codes adopted by reference by this Building Code, it shall be construed to mean the Building Official, except in matters rightfully under the jurisdiction of the *Fire Protection Code (Chapter VII)*. In addition, the fire official shall have the above-mentioned duties and powers where fire apparatus emergency access drives, fire suppression and fire alarm systems are concerned. Except as expressly set forth herein, the Building Official does not have the authority to waive any requirement of law.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

4-206. INTERNATIONAL BUILDING CODE, SECTION 104.10. MODIFICATIONS. Section 104.10 of the IBC is hereby amended to read as follows: **Modifications.** Wherever there are practical difficulties involved in carrying out the provisions of this Building Code, the building official shall have the authority to grant modifications for individual cases, upon application of the owner or owner's representative, provided the building official shall first find that special individual reason makes the strict letter of this Building Code impractical and the modification is in compliance with the intent and purpose of this Building Code and that such modification does not lessen health, accessibility, life and fire safety, or structural requirements. If such requested modification involves fire apparatus emergency access drives, fire suppression and/or fire alarm systems then the modification must also be approved by the fire official. The details of action granting modifications shall be recorded and entered in the files of codes administration.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

4-207. INTERNATIONAL BUILDING CODE, SECTION 104.11. ALTERNATIVE MATERIALS, DESIGN AND METHOD OF CONSTRUCTION AND EQUIPMENT.

Section 104.11 of the IBC is hereby amended to read as follows: **Alternative materials, design and method of construction and equipment.** The provisions of this Building Code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by this Building Code, provided that any such alternative has been approved. An alternative material, design or method of construction shall be approved where the building official finds that the proposed design is satisfactory and complies with the intent of the provisions of this Building Code, and that the material, method or work offered is, for the purpose intended, at least the equivalent of that prescribed in this Building Code in quality, strength, effectiveness, fire resistance, durability and safety. If such requested alternative material, design and/or method or equipment involves fire apparatus emergency access drives, fire suppression and/or fire alarm systems then the alternative must also be approved by the fire official.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

4-208.

INTERNATIONAL BUILDING CODE, SECTION 105.2. WORK EXEMPTED FROM PERMIT. Section 105.2 of the IBC is hereby amended to read as follows: **Work exempted from permit.** Exemptions from permit requirements of this Building Code shall not be deemed to grant authorization for any work to be done in any manner in violation of the provisions of this Building Code or any other laws or ordinances of this jurisdiction. Permits shall not be required for the following:

Building:

1. Retaining walls that are not over four (4) feet (1219 mm) in height measured from the bottom of the footing to the top of the wall, unless supporting a surcharge or impounding Class I, II or IIIA liquids.
2. Sidewalks and driveways not more than thirty (30) inches (762 mm) above adjacent grade, and not over any basement or story below and are not part of an accessible route and are not located in the public right-of-way.
3. Painting, papering, tiling, carpeting, cabinets, counter tops and similar finish work.
4. Temporary motion picture, television and theater stage sets and scenery.
5. Swings and other playground equipment accessory to detached one- and two-family dwellings.
6. Window awnings supported by an exterior wall that do not project more than thirty six (36) inches (914 mm) from the exterior wall and do not require additional support of Group R-3 and U occupancies.
7. Nonfixed and movable fixtures, cases, racks, counters and partitions not over five (5) feet nine (9) inches (1753 mm) in height.

Electrical:

1. Repairs and maintenance: Minor repair work, including the replacement of lamps and the replacement of smoke or carbon monoxide alarms, or the connection of approved portable electrical equipment to approved permanently installed receptacles.
2. Radio and television transmitting stations: The provisions of this Building Code shall not apply to electrical equipment used for radio and television

transmissions, but do apply to equipment and wiring for a power supply and the installations of towers and antennas.

3. Temporary testing systems: A permit shall not be required for the installation of any temporary system required for the testing or servicing of electrical equipment or apparatus.

Gas:

1. Portable heating appliance.
2. Replacement of any minor part that does not alter approval of equipment or make such equipment unsafe.

Mechanical:

1. Portable heating appliance.
2. Portable ventilation equipment.
3. Portable cooling unit.
4. Steam, hot or chilled water piping within any heating or cooling equipment regulated by this Building Code.
5. Replacement of any part that does not alter its approval or make it unsafe.
6. Portable evaporative cooler.
7. Self-contained refrigeration system containing ten (10) pounds or less of refrigerant and actuated by motors of one (1) horsepower or less.
8. Portable fuel cell appliances that are not connected to a fixed piping system and are not interconnected to a power grid.

Plumbing:

1. The stopping of leaks in drains, water, soil, waste or vent pipe, provided, however, that if any concealed trap, drain pipe, water, soil, waste or vent pipe becomes defective and it becomes necessary to remove and replace the same with new material, such work shall be considered as new work and a permit shall be obtained and inspection made as provided in this Building Code.
2. The clearing of stoppages or the repairing of leaks in pipes, valves or fixtures and the removal and reinstallation of water closets, provided such repairs do not involve or require the replacement or rearrangement of valves, pipes or fixtures.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Code 2000)
(Ord. 1711C; 03-23-98)

4-209. INTERNATIONAL BUILDING CODE, SECTION 105.3. APPLICATION FOR PERMIT. Section 105.3 of the IBC is hereby amended to read as follows:

(a) Application for permit.

To obtain a permit, the applicant shall first file an application therefore in writing on a form furnished by the building official for that purpose. Such application shall:

1. Identify and describe the work to be covered by the permit for which application is made.
2. Describe the land on which the proposed work is to be done by legal description, street address or similar description that will readily identify and definitely locate the proposed building or work.
3. Indicate the use and occupancy for which the proposed work is intended.
4. Be accompanied by construction documents and other information as required in Section 107.
5. State the valuation of the proposed work.

6. Be signed by the applicant, or the applicant's authorized agent.
7. Give such other data and information as required by the building official.

(b) Application for complete structure demolition permit.

To obtain a fifteen (15)-day complete structure demolition permit, the applicant shall first file an application therefore in writing on a form furnished by the building official for that purpose. Such application shall provide:

1. A site plan showing the location of the building or structure to be demolished and of all existing buildings on the property. The plan shall additionally show any necessary means of pedestrian protection as required by the Leawood Building Code.
2. The location where the demolition debris will be deposited.
3. The height and the total square footage of the building.
4. Evidence of required street closure permit.
5. The name and address of the owner of the building.
6. The type of equipment or method used to demolish the building.
7. Evidence that all public utilities have been disconnected.
8. Proof of rat-abating of any building at least ten days before the demolition may be required.
9. Proof of permission from the owner to demolish the building.
10. Evidence that proper erosion control will be provided for the site during demolition as well as during seeding and final grading of site.
11. Evidence that the structure has been inspected for asbestos. If asbestos is found, evidence shall be provided to indicate how the asbestos is to be removed and where it will be disposed.
11. Site plan, which shall indicate proposed grading and seeding.
12. Said permit will be issued in conjunction with permit for proposed new construction where applicable.

(c) Application for partial structure or interior demolition permit.

To obtain a thirty (30)-day partial structure or interior demolition permit, the applicant shall first file an application therefore in writing on a form furnished by the building official for that purpose. Such application shall provide:

1. Identify and describe the work to be covered by the permit for which application is made.
2. Describe the land on which the proposed work is to be done by legal description, street address or similar description that will readily identify and definitely locate the proposed building or work.
3. Indicate the use and occupancy for which the proposed work is intended.
4. Be accompanied by construction documents and other information as required by building official.
5. State the valuation of the proposed work.
6. Be signed by the applicant, or the applicant's authorized agent.
7. Give such other data and information as required by the building official.
8. Said permit will be issued in conjunction with permit for proposed new construction.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)

4-210. INTERNATIONAL BUILDING CODE, SECTION 105.5. EXPIRATION. Section 105.5 of the IBC is hereby amended to read as follows:

Expiration. Permits shall expire under the following circumstances:

- (a) Permits for new construction will expire in three hundred sixty five (365) days unless the work authorized by the permit is not commenced within one hundred eighty (180) days after issuance, in which case, the permit will expire in one hundred eighty (180) days. If the work is at any time during the permitting period, suspended or abandoned, then the permit shall expire on the earlier of its one year term, or one hundred eighty (180) days after the suspension or abandonment.
- (b) Moving permits shall expire five days after issuance.
- (c) Complete structure demolition permits shall expire fifteen (15) days after issuance.
- (d) Partial structure and interior demolition permits shall expire thirty (30) days after issuance.
- (e) Re-roof, fence, and general miscellaneous permits shall expire sixty (60) days after issuance.
- (f) Permits for decks, hot tubs, outdoor kitchens, patios, grading, and footing/foundations shall expire ninety (90) days after issuance.
- (g) Every other type of permit, not otherwise listed above, shall expire one hundred eighty (180) days after issuance.
- (h) For all permits other than moving or demolition permits, the building official is authorized to grant, in writing, one extension of time, for a period not exceeding the original length of the permit issued, but in no event longer than one hundred eighty (180) days. The extension shall be requested in writing prior to expiration of the term of the permit and justifiable cause demonstrated. The building official may only grant an extension upon finding that substantial progress has been made toward completion. Substantial progress means that the project is over fifty (50) percent complete and, in the opinion of the building official, the project applicant has the capability to finish the work permitted within the time period extension. If substantial progress has not been provided, the permit will expire. After a permit has expired a permit can be reissued, upon payment of reinstatement fees, for one extension of time for a period not exceeding the original length of the permit issued, but in no event longer than one hundred eighty (180) days.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

4-211. INTERNATIONAL BUILDING CODE, SECTION 107.1. SUBMITTAL DOCUMENTS, GENERAL. Section 107.1 of the IBC is hereby amended to read as follows: **General.** Construction documents, statement of special inspections, geotechnical report and other data shall be submitted in one or more sets with each permit application. At least five (5) hard copies and one (1) digital copy of plans shall be submitted for all new construction with at least three (3) hard copies and one (1) digital copy being submitted for all alteration projects. The construction documents shall be prepared by a registered design professional licensed by the State of Kansas. Where special conditions exist, the building official is authorized

to require additional construction documents to be prepared by a registered design professional.

EXCEPTION: The building official is authorized to waive the submission of construction documents and other data not required to be prepared by a registered design professional if it is found that the nature of the work applied for is such that review of construction documents is not necessary to obtain compliance with this Building Code.

(Ord. 2978; 01-21-20)

(Ord. 2593C; 12-03-12)

(Ord. 2291C; 02-04-08)

(Ord. 1930C; 01-22-02)

(Code 2000)

(Ord. 1711C; 03-23-98)

4-212. INTERNATIONAL BUILDING CODE, SECTION 107.2.2. FIRE PROTECTION SYSTEM SHOP DRAWINGS. Section 107.2.2 of the IBC is hereby amended to read as follows: **Fire protection system shop drawings.** Shop drawings and supporting documentation for the fire protection system(s), which shall include but not be limited to provisions for fire alarm systems and sprinkler systems, shall be submitted to the fire official and shall indicate conformance with this Building Code, the *Fire Protection Code (Chapter VII)*, and the construction documents. The shop drawings shall be approved prior to the start of system installation. Shop drawings shall contain all information as required by the referenced installation standards in this Building Code.

(Ord. 2978; 01-21-20)

(Ord. 2593C; 12-03-12)

(Ord. 2291C; 02-04-08)

(Ord. 1930C; 01-22-02)

(Code 2000)

(Ord. 1711C; 03-23-98)

4-213. INTERNATIONAL BUILDING CODE, SECTION 107.2.6. SITE PLAN. Section 107.2.6 of the IBC is hereby amended to read as follows: **Site Plan.** There shall be a site plan showing, to scale, the size and location of all the new construction and all existing structures on the site including easements, sewers, drains, utilities, etc., distances from lot lines, established street grades, and the proposed finished grades, and it shall be drawn in accordance with an accurate boundary line survey. All decks, balconies, overhangs, or other building protrusions shall be indicated and dimensioned. In the case of demolition, the plot plan shall show all construction to be demolished and the location and size of all existing structures and construction that are to remain on the site of the plot. Fire apparatus access roads provided and fire hydrant coverage as approved by the fire official shall be indicated as such on the site plan. The property owner or his or her agent shall certify to the building official that the top of the foundation for a building will be in conformance with the approved site plan, including building elevations, site grading, erosion control devices, and building setbacks. The building official is authorized to waive or modify the requirement for a site plan when the application for permit is for alteration or repair and does not affect the exterior features of the building.

(Ord. 2978; 01-21-20)

(Ord. 2593C; 12-03-12)

(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

- 4-214. **INTERNATIONAL BUILDING CODE, SECTION 108.1. GENERAL.** Section 108.1 of the IBC is hereby amended to read as follows: **Temporary Structures and Uses, General.** The building official is authorized to issue a permit for temporary structures and temporary uses. Such permits shall be limited as to time of service and are only allowed if authorized under the Leawood Development Ordinance and the provisions of this Building Code, the building official may grant extensions for these uses for demonstrated cause.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

- 4-215 **INTERNATIONAL BUILDING CODE, SECTION 108.2. CONFORMANCE.**
Repealed.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)
(Code 2000)
(Ord. 1711C; 03-23-98)

- 4-216 **INTERNATIONAL BUILDING CODE, SECTION 108.3. TEMPORARY POWER.**
Repealed.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
(Ord. 1930C; 01-22-02)

- 4-217. **INTERNATIONAL BUILDING CODE, SECTION 109.2. SCHEDULE OF PERMIT FEES.** Section 109.2 of the IBC is hereby amended to read as follows: **Schedule of permit fees.** On buildings, structures, electrical, gas, mechanical, elevator equipment, and plumbing systems or alterations or repairs requiring a permit, a fee for each permit shall be paid as required, in accordance with the City of Leawood Fee Schedule, adopted by Resolution of the Governing Body.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-218. INTERNATIONAL BUILDING CODE, SECTION 109.6. REFUNDS. Section 109.6 of the IBC is hereby amended to read as follows: **Refunds.** Unless specifically set forth herein, all fees paid are non-refundable. The building official may authorize refunding of any fee paid hereunder, which was erroneously paid or collected. The building official shall upon request authorize refunding of not more than eighty (80) percent of the permit fee paid when no work has been done under a permit issued in accordance with the Leawood Building Code. The building official shall upon request authorize refunding of not more than eighty (80) percent of the plan review fee paid when an application for a permit for which a plan review fee has been paid is withdrawn or canceled before any plan reviewing is done. The building official shall not authorize refunding of any fee paid except on written application filed by the original permit holder not later than one hundred eighty (180) days after the date of fee payment.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-219. INTERNATIONAL BUILDING CODE, SECTION 110.3. REQUIRED INSPECTIONS. Section 110.3 through 110.3.13.1 of the IBC is hereby amended to read as follows: **Required inspections.** The building official, upon notification, shall make the inspections set forth in Sections 110.3.1 through 110.3.13.

110.3.1 Footing and foundation inspection. Footing and foundation inspections shall be made after excavations for footings are complete and any required reinforcing steel is in place. For concrete foundations, any required forms shall be in place prior to inspection. Materials for the foundation shall be on the job, except where concrete is ready mixed in accordance with ASTM C 94, the concrete need not be on the job.

110.3.2 Concrete slab and under-floor inspection. Concrete slab and under-floor inspections shall be made after in-slab or under-floor reinforcing steel and building service equipment, conduit, piping accessories and other ancillary equipment items are in place, but before any concrete is placed or floor sheathing installed, including the subfloor.

110.3.3 Lowest floor elevation. In flood hazard areas, upon placement of the lowest floor, including the basement, and prior to further vertical construction, the elevation certification required in Section 1612.5 shall be submitted to the building official.

110.3.4 Frame inspection. Framing inspections shall be made after the roof deck or sheathing, all framing, fireblocking and bracing are in place and pipes, chimneys and vents to be concealed are complete and the rough electrical, plumbing, heating wires, pipes and ducts are approved.

110.3.5 Lath and gypsum board inspection and gypsum panel product inspection. Lath and gypsum board and gypsum panel product inspections shall be made after lathing, gypsum board and gypsum panel products, interior and exterior, are in place, but before any plastering is applied or gypsum board and gypsum panel product joints and fasteners are taped and finished.

EXCEPTION: Gypsum board and gypsum panel products that are not part of a fire-resistance-rated assembly or a shear assembly.

110.3.6 Weather-exposed balcony and walking surface waterproofing. Where balconies or other elevated walking surfaces are exposed to water from direct or blowing rain, snow or irrigation, and the structural framing is protected by

an impervious moisture barrier, all elements of the impervious moisture barrier system shall not be concealed until inspected and approved.

EXCEPTION: Where special inspections are provided in accordance with Section 1705.1.1, Item 3.

110.3.7 Fire- and smoke-resistant penetrations. Protection of joints and penetrations in fire-resistance-rated assemblies, smoke barriers and smoke partitions shall not be concealed from view until inspected and approved.

110.3.8 Energy efficiency inspections. Inspections shall be made to determine compliance with Chapter 13 and shall include, but not be limited to, inspections for: envelope insulation *R* and *U* values, fenestration *U* value, duct system *R* value, and HVAC and water-heating equipment efficiency.

110.3.9 Roofing inspections. Roofing inspections shall be made at the mid-point of roofing installation and after roofing installation is complete.

110.3.10 Other inspections. In addition to the inspections specified above, the building official is authorized to make or require other inspections of any construction work to ascertain compliance with the provisions of this Building Code and other laws that are enforced by the department of building safety.

110.3.11 Special inspections. For special inspections, see Chapter 17.

110.3.12 Fire protection inspections. Inspection of all fire protection systems. The fire official or his or her designee shall make this inspection.

110.3.13 Final inspection. The final inspection shall be made after all work required by the building permit is completed.

110.3.13.1 Flood hazard documentation. If located in a flood hazard area, documentation of the elevation of the lowest floor as required in Section 1612.4 shall be submitted to the building official prior to the final inspection.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-220.

INTERNATIONAL BUILDING CODE, SECTION 111.1. USE AND OCCUPANCY.

Section 111.1 of the IBC is hereby amended to read as follows: **Use and occupancy.** No building or structure shall be used or occupied, and no change in the existing occupancy classification of a building or structure or portion thereof shall be made until the building official has issued a certificate of occupancy therefore as provided herein. Issuance of a certificate of occupancy shall not be construed as an approval of a violation of the provisions of the *Leawood Building Code* or of other ordinances of the City of Leawood.

Exception: Certificates of occupancy are not required for work exempt from permits under Section 105.2.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-221.

INTERNATIONAL BUILDING CODE, SECTION 111.2. CERTIFICATE ISSUED.

Section 111.2 of the IBC is hereby amended to read as follows: **Certificate Issued.** After the building official inspects the building or structure and finds no violations of the provisions of this Building Code, *Leawood Development Ordinance*, *Fire Protection Code (Chapter VII)*, *Property Maintenance Code (Chapter VIII)* or other laws that are enforced by the department of building safety, the building official shall issue a certificate of occupancy that contains the following:

1. The building permit number.
2. The address of the structure.
3. The name and address of the owner or the owner's authorized agent.
4. A description of that portion of the structure for which the certificate is issued.
5. A statement that the described portion of the structure has been inspected for compliance with the requirements of this Building Code for the occupancy and division of occupancy and the use for which the proposed occupancy is classified.
6. The name of the building official.
7. The name of the fire official.
8. The edition of the code under which the permit was issued.
9. The use and occupancy, in accordance with the provisions of Chapter 3.
10. The type of construction as defined in Chapter 6.
11. The design occupant load.
12. If an automatic sprinkler system is provided, whether the sprinkler system is required.
13. Any special stipulations and conditions of the building permit.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-222.

INTERNATIONAL BUILDING CODE, SECTION 111.3. TEMPORARY OCCUPANCY.

Section 111.3 of the IBC is hereby amended to read as follows: **Temporary occupancy.** The building official is authorized to issue a Temporary Certificate of Occupancy (TCO) before the completion of the entire work covered by the permit, provided that such portion or portions shall be occupied safely. The Building Official shall set a time period during which the temporary certificate of occupancy is valid, provided, however that such time period shall not exceed sixty (60) days. The Building Official is authorized to renew the Temporary Certificate of Occupancy for two (2) additional periods not exceeding sixty (60) days for each renewal.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

- 4-223. INTERNATIONAL BUILDING CODE, SECTION 112.3. AUTHORITY TO DISCONNECT SERVICE UTILITIES.** Section 112.3 of the IBC is hereby amended to read as follows: **Authority to Disconnect Service Utilities.** The building official shall have the authority to authorize disconnection of utility service to the building, structure or system regulated by this *Building Code, Fire Protection Code, or Property Maintenance Code*, or otherwise in violation of the Code of the City of Leawood, 2000, or in case of emergency where necessary to eliminate an immediate hazard to life or property or where such utility connection has been made without the approval required by Section 112.1 or 112.2. The building official shall notify the serving utility, and wherever possible the owner and occupant of the building, structure or service system of the decision to disconnect before taking such action. If not notified prior to disconnecting, the owner or occupant of the building, structure or service system shall be notified in writing, as soon as practical thereafter.
- (Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
- 4-224. INTERNATIONAL BUILDING CODE, SECTION 113. BOARD OF APPEALS.** Sections 113.1 through 113.3 of the IBC are hereby omitted and deleted in their entirety. [See Section 4-105 et seq.]
- (Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
- 4-225. INTERNATIONAL BUILDING CODE, SECTION 114.4. VIOLATION PENALTIES.** Section 114.4 of the IBC is hereby amended to read as follows: **Violation Penalties.** Any person who violates a provision of this code or this Article or fails to comply with any of the requirements thereof or who erects, constructs, alters or repairs a building or structure in violation of the approved construction documents or directive of the building official or of a permit or certificate issued under the provisions of this code is guilty of a public offense, punishable by a fine of not more than five hundred dollars (\$500) or by imprisonment not exceeding thirty (30) days or both such fine and imprisonment. Each day that the violation continues shall be deemed a separate offense.
- (Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
- 4-226 INTERNATIONAL BUILDING CODE, SECTION 116. UNSAFE STRUCTURES AND EQUIPMENT. *Repealed.***
- (Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
- 4-226A INTERNATIONAL BUILDING CODE, SECTION 305.2.3. SIX OR FEWER CHILDREN IN A DWELLING UNIT.** Section 305.2.3 of the IBC is hereby amended to read as follows: **Six or fewer children in a dwelling unit.** A facility such as the above within a dwelling unit and having six or fewer children receiving such day care shall comply with the Johnson County Home Daycare Handbook

and shall be classified as a Group R-3 occupancy or shall comply with the International Residential Code. No sprinkler system shall be required.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)

4-226B. INTERNATIONAL BUILDING CODE, SECTION 423.2. STORM SHELTERS, GENERAL. Section 423.2 of the IBC is hereby amended to read as follows: **Construction.** In addition to other applicable requirements in this code, storm shelters shall be constructed in accordance with ICC-500. Buildings or structures that are also designated as emergency shelters shall also comply with Table 1604.5 as Risk Category IV structures.

The following are exceptions and additions to ICC-500 requirements.

1. Sanitation facilities shall only be required for Community Shelters as defined by the ICC-500. Community Shelters with a design occupant load of 100 or less shall be permitted to provide only 1 toilet facility.
2. Community Shelters shall be provided with fixed seating for 1/3 of the design occupant load.
3. Community Shelters shall be provided with an approved first aid kit.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)

4-226C. INTERNATIONAL BUILDING CODE, SECTION 423.4. GROUP E, R-1, R-2, R-3, R-4, I-1, OR I-2 OCCUPANCIES. Section 423.4 of the IBC is hereby amended to read as follows: **Section 423.4. Group E, R-1, R-2, R-3, R-4, I-1, or I-2 Occupancies.** In areas where the shelter design wind speed for tornados is 250 mph in accordance with Figure 304.2(1) of ICC 500, all Group E occupancies with an occupant load of 50 or more, and all R-1, R-2, R-3, R-4, I-1, or I-2 occupancies of any occupant load shall have a storm shelter constructed in accordance with ICC 500 as modified and adopted by the City.

EXCEPTIONS:

1. Group E occupancies accessory to places of religious worship.
2. Buildings meeting the requirements for shelter design in ICC 500.

(Ord. 2978; 01-21-20)

4-226D INTERNATIONAL BUILDING CODE, SECTION 423.4.1. REQUIRED OCCUPANT CAPACITY. Section 423.4.1 of the IBC is hereby amended to read as follows: **Section 423.4.1. Required Occupant Capacity.** The required occupant capacity of the storm shelter shall include all buildings on the site. For an E occupancy, the shelter capacity shall be the greater of the following:

1. The total occupant load of the classrooms, vocational rooms and offices in the Group E occupancy.
2. The occupant load of any indoor assembly space that is associated with the Group E occupancy.

EXCEPTIONS:

1. Where a new building is being added on an existing site, and where the new building is not of sufficient size to accommodate the required

occupant capacity of the storm shelter for all of the buildings on the site, the storm shelter shall at a minimum accommodate the required occupant capacity for the new building.

2. Where approved by the code official, the required occupant capacity of the shelter shall be permitted to be reduced by the occupant capacity of any existing storm shelters on site.

(Ord. 2978; 01-21-20)

4-226E. INTERNATIONAL BUILDING CODE, SECTION 429. BASEMENT REQUIRED.

A new Section 429 is hereby added to read as follows: **Basement Required.** Buildings classified as apartment houses under Group R-2 occupancies as defined in the Building Code shall be constructed with a basement.

EXCEPTIONS:

- (a) The provisions of this section shall not apply to Group R-2 occupancy buildings which are designed and constructed specifically for the use of disabled individuals and which contain a storm shelter or safe room constructed in accordance with IBC Section 423.
- (b) The provisions of this section shall not apply to Group R-2 occupancy buildings when it would be impractical to construct a basement in light of subsurface conditions verified by an engineer and when such dwellings contain a storm shelter or safe room constructed in accordance with IBC Section 423.
- (c) The provisions of this section shall not apply to the repair or reconstruction of any existing Group R-2 occupancy building, unless such building is being 100% reconstructed.

(Ord. 2978; 01-21-20)

(Ord. 2593C; 12-03-12)

4-227. INTERNATIONAL BUILDING CODE, SECTION 903.2. WHERE REQUIRED.

Section 903.2 of the IBC is hereby amended to read as follows: An approved automatic sprinkler system shall be provided in all buildings regulated by the *Leawood Building Code*.

EXCEPTIONS:

- (a) Any occupancy specifically exempted from automatic sprinkler requirements by Kansas Statute or Administrative Regulation.
- (b) New or existing buildings regulated by the International Residential Code that are within 500 feet of an approved fire hydrant.
- (c) Group S-2 Open Parking Garages, and all Group U occupancies.
- (d) All new buildings for occupancy Groups other than H, I, and R with a total area less than one thousand (1,000) square feet.
- (e) Rooms or areas protected with an approved automatic fire detection system in accordance with Section 907.2 of the International Building Code that will respond to visible or invisible particles of combustion if: (1) application of water, or flame and water, to such room would constitute a

serious life or fire hazard; or (2) such rooms or area are of noncombustible construction with wholly noncombustible contents.

- (f) Temporary buildings allowed under the Leawood Development Ordinance for a period not to exceed two years.
- (g) Renovations or improvements to existing buildings where no occupancy Group classification change occurs and/or no additional building area is being created, and the cost of the sprinkler system installation downstream of the riser would exceed twenty percent (20) of the total cost of renovation. In such cases, an approved sprinkler or other life safety improvement to the building may be required, provided that the cost of such requirement will not exceed twenty percent (20) of the cost of the renovation.
- (h) In home day care facilities for the care of 6 or fewer children for less than 12 hours per day.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-227A. INTERNATIONAL BUILDING CODE, SECTION 903.3. INSTALLATION REQUIREMENTS. Section 903.3 of the IBC is hereby amended to read as follows: **903.3 Installation requirements.** Automatic sprinkler systems shall be designed and installed in accordance with Sections 903.3.1 through 903.3.8 of this code. In addition, automatic sprinkler systems shall be protected in accordance with the adopted International Plumbing Code.

(Ord. 2978; 01-21-20)

4-228. INTERNATIONAL BUILDING CODE, SECTION 905.3. GENERAL. Section 905.3 of the IBC is hereby amended to read as follows: An approved Class I standpipe system shall be required in all occupancies where the travel distance from the nearest point of approved fire department access to any point within the building exceeds 200 feet. All Class I standpipe systems may be combined with sprinkler system piping.

EXCEPTION: Standpipe systems are not required in Group R-3, R-4 and U occupancies as applicable in 101.2.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-228A INTERNATIONAL BUILDING CODE, TABLE 1004.1.2. MAXIMUM FLOOR AREA ALLOWANCES PER OCCUPANT. *Repealed.*

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)

4-229 INTERNATIONAL BUILDING CODE, SECTION 1010.4. PHYSICAL SECURITY. A new Section 1010.4 of the IBC is hereby added to read as follows: **1010.4. Purpose.** The purpose of this Section 1010.4 is to establish minimum standards that incorporate physical security to make dwelling units resistant to unlawful entry.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)

(Ord. 2291C; 02-04-08)

4-230. INTERNATIONAL BUILDING CODE, SECTION 1010.4.1. SCOPE. A new Section 1010.4.1 of the IBC is hereby added to read as follows:

1010.4.1 Scope. The provisions of Section 1010.4.1 shall apply to all new structures and to alterations, additions, and repairs as set forth in the International Existing Building Code adopted in Section 4-701 of this Code.

(Ord. 2978; 01-21-20)

(Ord. 2593C; 12-03-12)

(Ord. 2291C; 02-04-08)

4-231. INTERNATIONAL BUILDING CODE, SECTION 1010.4.2. DOORS. A new Section 1010.4.2 of the IBC is hereby added to read as follows:

1010.4.2 Doors. Except for vehicular access doors, all exterior swinging doors of residential buildings and attached garages, including the doors leading from the garage area into the dwelling unit, shall comply with following for the type of door installed.

(a) Wood doors. Where installed, exterior wood doors shall be of solid core construction such as high-density particleboard, solid wood, or wood block core with a minimum thickness of one and three-fourths inches (1 $\frac{3}{4}$ ") at any point. Doors with panel inserts shall be solid wood. The panels shall be a minimum of one inch (1") thick. The tapered portion of the panel that inserts into the groove of the door shall be a minimum of one-quarter inch (1/4") thick. The groove shall be a dado groove or applied molding construction. The groove shall be a minimum of one-half inch (1/2") in depth.

(b) Steel doors. Where installed, exterior steel doors shall be a minimum thickness of 24 gauge.

(c) Fiberglass doors. Fiberglass doors shall have a minimum skin thickness of one-sixteenth inch (1/16") and have reinforcement material at the location of the deadbolt.

(d) Double doors. Where installed, the inactive leaf of an exterior double door shall be provided with flush bolts having an engagement of not less than one inch into the head and threshold of the doorframe.

(e) Sliding doors. Where installed, exterior sliding doors shall comply with all of the following requirements:

1. Sliding door assemblies shall be installed to prevent the removal of the panels and the glazing from the exterior with the installation of shims or screws in the upper track.

2. All sliding glass doors shall be equipped with a secondary locking device consisting of a metal pin or a surface mounted bolt assembly. Metal pins shall be installed at the intersection of the inner and outer panels of the inside door and shall not penetrate the frame's exterior surface. The surface mounted bolt assembly shall be installed at the base of the door.

(Ord. 2978; 01-21-20)

(Ord. 2593C; 12-03-12)

(Ord. 2291C; 02-04-08)

4-232. INTERNATIONAL BUILDING CODE, SECTION 1010.4.3. DOOR FRAMES. A new Section 1010.4.3 of the IBC is hereby added to read as follows:

1010.4.3 Door frames. The exterior door frames shall be installed prior to a rough-in inspection. Door frames shall comply with the following for the type of assembly installed:

(a) Wood frames. Wood door frames shall comply with all of the following requirements:

1. All exterior door frames shall be set in frame openings constructed of double studding or equivalent construction, including garage doors, but excluding overhead doors. Door frames, including those with sidelights, shall be reinforced in accordance with ASTM F476-84 Grade 40.
2. In wood framing horizontal blocking shall be placed between studs at the door lock height for three (3) stud spaces or equivalent bracing on each side of the door opening.

(b) Steel frames. All exterior door frames shall be constructed of eighteen (18) gauge or heavier steel, and reinforced at the hinges and strikes. All steel frames shall be anchored to the wall in accordance with manufacturer specifications. Supporting wall structures shall consist of double studding or framing of equivalent strength. Frames shall be installed to eliminate tolerances inside the rough opening.

(c) Door jambs:

1. Door jambs shall be installed with solid backing in a manner so that no void exists between the strike side of the jamb and the frame opening for a vertical distance of twelve inches (12") each side of the strike. Filler material shall consist of a solid wood block.
2. Door stops on wooden jambs for in-swinging doors shall be of one-piece construction. Jambs for all doors shall be constructed or protected so as to prevent violation of the strike.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-233.

INTERNATIONAL BUILDING CODE, SECTION 1010.4.4. DOOR HARDWARE.

A new Section 1010.4.4 of the IBC is hereby added to read as follows:

1010.4.4 Door hardware. Exterior door hardware shall comply with the following:

(a) Hinges. Hinges for exterior door hardware shall comply with the following:

1. At least two (2) screws, three inches (3") in length, penetrating at least one inch (1") into wall structure shall be used. Solid wood fillers or shims shall be used to eliminate any space between the wall structure and door frame behind each hinge.
2. Hinges for out-swinging doors shall be equipped with mechanical interlock to preclude the removal of the door from the exterior.

(b) Strike plates. Exterior door strike plates shall be a minimum of eighteen (18) gauge metal with four (4) offset screw holes. Strike plates shall be attached to wood with not less than three inch (3") screws, which shall have

a minimum of one inch (1") penetration into the nearest stud. Note: For side lighted units, refer to Section (f) below.

- (c) **Escutcheon plates.** All exterior doors shall have escutcheon plates or wraparound door channels installed around the lock protecting the door's edge.
- (d) **Locks.** Exterior doors shall be provided with a locking device complying with one of the following:
Single Cylinder Deadbolt shall have a minimum projection of one inch (1"). The deadbolt shall penetrate at least three-fourths inch (3/4") into the strike receiving the projected bolt. The cylinder shall have a twist-resistant, tapered hardened steel cylinder guard. The cylinder shall have a minimum of five (5) pin tumblers, shall be connected to the inner portion of the lock by solid metal connecting screws at least one-fourth (1/4) inch in diameter and two and one-fourth (2 1/4) inches in length. Bolt assembly (bolt housing) unit shall be of single piece construction. All deadbolts shall meet ANSI grade 2 specifications.
- (e) **Entry vision and glazing.** All main or front entry doors to dwelling units shall be arranged so that the occupant has a view of the area immediately outside the door without opening the door. The view may be provided by a door viewer having a field of view of not less than one hundred eighty degrees (180°) through windows or through view ports.
- (f) **Side lighted entry doors.** Side light door units shall have framing of double stud construction or equivalent construction complying with Sections 1008.4.3.(a), (b) and (c). The doorframe that separates the door opening from the side light, whether on the latch side or the hinge side, shall be double stud construction or equivalent construction complying with Sections 1008.4.3. (a) and (b). Double stud construction or construction of equivalent strength shall exist between the glazing unit of the side light and wall structure of the dwelling.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-234.

INTERNATIONAL BUILDING CODE, SECTION 1010.4.5. STREET NUMBERS.

A new Section 1010.4.5 of the IBC is hereby added to read as follows:

1010.4.5 Street numbers. Street numbers shall be as approved by the Fire Official so as to provide legible property identification at the distance of approach of emergency vehicles under conditions which can be normally anticipated but shall be 6" minimum and not exceed 12" in height and be of starkly contrasting color to background. Street names shall not be required and all numbers shall be characters and not written words and shall be horizontal in orientation.

EXCEPTION: All occupancies governed by the International Residential Code.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-235. INTERNATIONAL BUILDING CODE, SECTION 1010.4.6. EXTERIOR LIGHTING. A new Section 1010.4.6 of the IBC is hereby added to read as follows:
1010.4.6 Exterior lighting. Exterior lighting shall comply with NFPA National Electric Code, 2017, Section 210.70.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-236. INTERNATIONAL BUILDING CODE, SECTION 1016.2. EGRESS THROUGH INTERVENING SPACES. Section 1016.2 of the IBC is hereby amended to read as follows:

1016.2 Egress through intervening spaces. Egress through intervening spaces shall comply with this section.

1. Exit access through an enclosed elevator lobby is permitted. Access to not less than one of the required exits shall be provided without travel through the enclosed elevator lobbies required by Section 3006. Where the path of exit access travel passes through an enclosed elevator lobby, the level of protection required for the enclosed elevator lobby is not required to be extended to the exit unless direct access to an exit is required by other sections of this code.
2. Egress from a room or space shall not pass through adjoining or intervening rooms or areas, except where such adjoining rooms or areas and the area served are accessory to one or the other, are not a Group H occupancy and provide a discernible path of egress travel to an exit.
EXCEPTION: Means of egress are not prohibited through adjoining or intervening rooms or spaces in a Group H, S or F occupancy where the adjoining or intervening rooms or spaces are the same or a lesser hazard occupancy group.
3. Egress shall not pass through kitchens, storage rooms, closets or spaces used for similar purposes.

EXCEPTIONS:

1. Means of egress are not prohibited through a kitchen area serving adjoining rooms constituting part of the same dwelling unit or sleeping unit.
2. Means of egress are not prohibited through stockrooms in Group M occupancies when all of the following are met:
 - 2.1 The stock is of the same hazard classification as that found in the main retail area;
 - 2.2 Not more than 50 percent of the exit access is through the stockroom;
 - 2.3 The stockroom is not subject to locking from the egress side; and
 - 2.4 There is a demarcated, minimum 44-inch wide (1118 mm) aisle defined by full or partial height fixed walls or similar construction that will maintain the required width and lead directly from the retail area to the exit without obstructions.
4. An exit access shall not pass through a room that can be locked to prevent egress.

5. Means of egress from dwelling units or sleeping areas shall not lead through other sleeping areas, toilet rooms or bathrooms.
6. Means of egress from the showroom floor in Type M occupancies shall not include any space which also serves as a point of delivery for stock, or for the staging of stock awaiting placement, or for trash awaiting removal from the occupancy, unless such area is designed to remain open to the showroom floor from which exiting is required.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-236A. INTERNATIONAL BUILDING CODE, SECTION 1202.1. VENTILATION GENERAL. Section 1202.1 of the IBC is hereby amended to read as follows:
1203.1 General. Buildings shall be provided with natural ventilation in accordance with Section 1202.5, or mechanical ventilation in accordance with the International Mechanical Code.

Where the air infiltration rate in a dwelling unit is less than 3 air changes per hour where tested with a blower door at a pressure 0.2 inch w.c. (50 Pa) in accordance with Section 402.4.1.2 of the International Energy Conservation Code – Residential Provisions, the dwelling unit shall be ventilated by mechanical means in accordance with Section 403 of the International Mechanical Code. Ambulatory care facilities and Group I-2 occupancies shall be ventilated by mechanical means in accordance with Section 407 of the International Mechanical Code.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)

4-237. INTERNATIONAL BUILDING CODE, SECTION 1501.1. SCOPE. Section 1501.1 of the IBC is hereby amended to read as follows: **1501.1 Scope.** The provisions of this chapter shall govern the design, materials, construction and quality of roof assemblies, and rooftop structures. All roof covering assemblies shall comply with the *Leawood Development Ordinance*.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-237A. INTERNATIONAL BUILDING CODE, SECTION 1511.1. GENERAL. Section 1511.1 of the IBC is hereby amended to read as follows: **General.** Materials and methods of application used for recovering or replacing an existing roof covering shall comply with the *Leawood Development Ordinance*. Such materials and methods of application shall also comply with the requirements of Chapter 15 of the International Building Code incorporated herein.

EXCEPTIONS:

1. Roof replacement or roof recover of existing low-slope roof coverings shall not be required to meet the minimum design slope requirement of one-quarter unit vertical in 12 units horizontal (2-percent slope) in Section 1507 for roofs that provide positive roof drainage.
2. Recovering or replacing an existing roof covering shall not be required to meet the requirement for secondary (emergency overflow) drains or scuppers in Section 1502 for roofs that provide for positive roof drainage. For the purposes

of this exception, existing secondary drainage or scupper systems required in accordance with this code shall not be removed unless they are replaced by secondary drains or scuppers designed and installed in accordance with Section 1502.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)

4-237B **INTERNATIONAL BUILDING CODE, SECTION 1612.3. ESTABLISHMENT OF FLOOD HAZARD AREAS.** Section 1612.3 of the IBC is hereby amended to read as follows: **1612.3 Establishment of Flood Hazard Areas.** The flood hazard map shall include areas of special flood hazard as identified by the Federal Emergency Management Agency. The flood hazard map shall include the most current Flood Insurance Rate Map (FIRM) and Flood Boundary and Floodway Map (FBFM). These maps and supporting data are hereby adopted by reference and declared to be part of this section. Additional flood hazard maps can be adopted at the discretion of the Governing Body of the City of Leawood.

(Ord. 2978; 01-21-20)

4-238. **INTERNATIONAL BUILDING CODE, TABLE 2902.1. MINIMUM NUMBER OF REQUIRED PLUMBING FIXTURES.** Table 2902.1 of the IBC is hereby amended to provide the following footnotes:

- (a) The fixtures shown are based on one fixture being the minimum required for the number of persons indicated or any fraction of the number of persons indicated. The number of occupants shall be determined by the *International Building Code*.
- (b) Toilet facilities for employees shall be separate from facilities for inmates or patients.
- (c) A single-occupant toilet room with one water closet and one lavatory serving not more than two adjacent patient sleeping units shall be permitted where such room is provided with direct access from each patient room and with provisions for privacy.
- (d) The occupant load for seasonal outdoor seating and entertainment areas shall be included when determining the minimum number of facilities required.
- (e) The minimum number of required drinking fountains shall comply with Table 2902.1 and Chapter 11.
- (f) Drinking fountains are not required for an occupant load of 15 or fewer.
- (g) Service sinks are not required for business occupancies with an occupant load of 15 or fewer.
- (h) A drinking fountain is not required in M occupancies with an occupant load less than 50.
- (i) A service sink is not required in M occupancies with an occupant load less than 50.
- (j) The required number and type of plumbing fixtures for outdoor swimming pools shall be in accordance with Section 609 of the International Swimming Pool and Spa Code as adopted in Section 4-1001 of this Code.

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

- 4-239. INTERNATIONAL BUILDING CODE, SECTION 3001.6. ACCEPTANCE INSPECTIONS.** A new Section 3001.6 of the IBC is hereby added to read as follows: **Acceptance Inspections.** All elevator equipment shall have an acceptance inspection and test performed and approved in accordance with ASME A17.1/ CSA B44 requirements. Prior to the issuance of a Certificate of Occupancy, a copy of this inspection shall be forwarded to the City of Leawood.
(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
- 4-240. INTERNATIONAL BUILDING CODE, SECTION 3001.7, PERIODIC INSPECTIONS.** A new Section 3001.7 of the IBC is hereby added to read as follows: **Periodic Inspections.** All existing elevator equipment shall have a periodic inspections and testing performed and approved in accordance with ASME A17.3/ CSA B44 requirements. A copy of these tests shall be forwarded to the City of Leawood.
(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
- 4-240A. INTERNATIONAL BUILDING CODE, SECTION 3001.8. CERTIFICATION OF INSPECTION REQUIRED.** A new Section 3001.8 of the IBC is hereby added to read as follows: **Certification of Inspection Required.** It shall be unlawful to operate any elevator, dumbwaiter, escalator, or moving walk without a current certificate of inspection provided by a Qualified Elevator Inspector who is certified by the National Association of Elevator Safety Authorities or other similar certification from another nationally recognized organization.
(Ord. 2978; 01-21-20)
- 4-240B. INTERNATIONAL BUILDING CODE, SECTION 3001.9. EXISTING ELEVATORS.** A new Section 3001.9 of the IBC is hereby added to read as follows: **Existing Elevators.** In addition to all other applicable Existing Building Code requirements, existing elevators shall comply with ASME A17.3/ CSA B44.
(Ord. 2978; 01-21-20)
- 4-241. INTERNATIONAL BUILDING CODE, SECTION 3403.6. ELEVATORS.**
Repealed.
(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)
- 4-241A. INTERNATIONAL BUILDING CODE, SECTION 3404.7. ELEVATORS.**
Repealed.
(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
- 4-242. INTERNATIONAL BUILDING CODE, SECTION 3410.2. LEAWOOD DEVELOPMENT ORDINANCE CONFORMANCE.** *Repealed.*
(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)

4-243. INTERNATIONAL BUILDING CODE, SECTION 3410.3. DUTIES OF STRUCTURE MOVING PERMITTEE. *Repealed.*

(Ord. 2978; 01-21-20)
(Ord. 2593C; 12-03-12)
(Ord. 2291C; 02-04-08)